








RAPID[®] asortimentas

Galvutės tipai, specifikacijos, padengimai

		Countersunk head		Wafer head	SuperSenkFix	Dual
		≤ 25 mm	≥ 30 mm			
						
Ø 3.0	Torx	T10		–	–	–
	Length	16 – 45 mm		–	–	–
	Thread	EG*	HiLo*	–	–	–
	Under-head	Milling pockets		–	–	–
Ø 3.5	Torx	T20		–	–	–
	Length	16 – 50 mm		–	–	–
	Thread	EG	HiLo	–	–	–
	Under-head	Milling pockets		–	–	–
Ø 4.0	Torx	T20		–	–	–
	Length	20 – 70 mm		–	–	–
	Thread	EG	HiLo	–	–	–
	Under-head	Milling pockets		–	–	–
Ø 4.5	Torx	T20		–	–	–
	Length	20 – 80 mm		–	–	–
	Thread	EG	HiLo	–	–	–
	Under-head	Milling pockets		–	–	–
Ø 5.0	Torx	T25		–	–	–
	Length	20 – 120 mm		–	–	–
	Thread	EG	HiLo	–	–	–
	Under-head	Milling pockets		–	–	–
Ø 6.0	Torx	T30		–	–	–
	Length	50 – 300 mm	60 – 300 mm	80 – 300mm	–	
	Thread	–	HiLo		–	
	Under-head	Milling pockets	smooth	Cone	–	
Ø 8.0	Torx	–	T40	T30	–	
	Length	80 – 500 mm	80 – 500 mm	80 – 400 mm	50 – 400 mm	
	Thread	–	HiLo		–	
	Under-head	–	Milling pockets	smooth	Cone	Cone
Ø 10.0	Torx	–	T50	T40	–	
	Length	80 – 500 mm	100 – 500 mm	120 – 400 mm	60 – 400 mm	
	Thread	–	HiLo		–	
	Under-head	–	Milling ribs	smooth	Cone	Cone
Ø 12.0	Torx	–	T50	–	T40	
	Length	100 – 400 mm	–	–	80 – 400 mm	
	Thread	–	EG	–	EG	
	Under-head	–	Milling ribs	–	Cone	
Surface		YellWin 500+ 			BlueWin 700+ 	BlueWin 

* EG: Single thread | HiLo: Dual thread